

Croda Oilfield

PRODUCT DATA

Pripol™ 1017

Polymerised Fatty Acid

Dimer fatty acid suitable for use in a wide range of industrial and oilfield applications as additive, emulsifier, corrosion inhibitor or boundary lubricant.

Physical properties

Typical values (not a specification).

Test	Units	Typical Value
Density	g/ml at 25°C	0.950
Dynamic viscosity	25°C mPa.s	8000
Flash point	°C (PMCC)	275
Physical form	25°C	Liquid
Solubility		Oil

Further information

Croda sales and distribution are coordinated through an extensive worldwide network of associates and agents. If you would like product samples, formulation advice, or technical assistance, please contact your nearest Croda regional office, or visit our website www.croda.com/oilfield

Europe, Middle East, Africa
Croda Europe Ltd
Tel +44 (0)1405 860551
Fax +44 (0)1405 861767
email: oilfield@croda.com

North America
Croda Inc, USA
Tel +1 732 417 0800
Fax +1 732 417 0804
email: marketing-usa@croda.com

Latin America
Croda do Brazil Ltda
Tel +55 (0)19 3765-3500
Fax +55 (0)19 3765-3536
email: marketingla@croda.com

Asia Pacific
Croda Singapore
Tel +65 65519600
Fax +65 65519550
email: is-asia@croda.com

Non-warranty

The information in this publication is believed to be accurate and is given in good faith, but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation or warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties of merchantability, fitness for a particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark and designs. Any trademarks identified herein are trademarks of the Croda group of companies.
©2010 Croda Europe Ltd

CRODA
Geo Technologies